



GOODYEAR Ultra FE 0W30

GOODYEAR ULTRA FE 0W-30 is a high-performance full synthetic motor oil, suitable for gasoline, LPG or diesel engines with or without turbo, where the above specifications are required. It helps to provide performance and wear protection under severe conditions. The state-of-the-art additive package helps to mitigate LSPI and keeps the engine clean from dirt, sludge, and deposits. The low viscosity fluidity make for a perfect cold start, fast response, and additional power from the engine.

SPECIFICATIONS

- Exceeded SP
- ACEA C2 / C3
- MB 229.61 / 229.62 / 229.52
- VW 504 00 / 507 00
- BMW LL 12-FE / LL 04
- Opel OV0401547
- Ford WSS-M2C950A / 963A1
- VOLVO VCC 95200377
- Porsche C30

PACKAGING

1L can (12 x 1L carton)

TYPICAL CHARACTERISTICS

Test Items	Test Method	Result
Appearance	VISUAL	Clear
Density @ 15°C, Kg/L	ASTM D4052	0.8390
Viscosity @ 40°C, cSt	ASTM D445	62.65
Viscosity @ 100°C, cSt	ASTM D445	11.15
Viscosity Index	ASTM D2270	173
ASTM Color	ASTM D6045	L2.5
TBN mg KOH/g	ASTM D2896	8.5
Pour Point °C	ASTM D97	-45
Flash Point °C	ASTM D92	222
CCS @ -35°C, cP	ASTM D5293	5964

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.