



GOODYEAR SUPREME 10W-40

GOODYEAR SUPREME 10W-40 provides maximum protection for modern engine technologies, ensuring smooth operation even under the most severe driving conditions. The superior oxidation and thermal stability of GOODYEAR SUPREME 10W-40 prevent sludge build-up and protect critical engine components, while its friction-reducing properties improve fuel efficiency and reduce engine wear.

GOODYEAR SUPREME 10W-40 is ideal for vehicles requiring high-performance lubrication and is especially recommended for engines meeting the following specifications: API SP, API SN Plus, API SN, and lower-grade specifications.

SPECIFICATIONS

API SP (approved)

API SN Plus (approved)

API SN, SM, SL, SJ

TYPICAL CHARACTERISTICS

Test Items	Test Method	Result
Appearance	VISUAL	Clear
Sp. Gravity @20°C	ASTM D4052	0.8605
Viscosity @ 40°C, cSt	ASTM D445	94.40
Viscosity @ 100°C, cSt	ASTM D445	14.22
Viscosity Index	ASTM D2270	155
ASTM Color	ASTM D1500	L2.5
TBN mg KOH/g	ASTM D2896	6.89
Pour Point °C	ASTM D6749	-33
Flash Point °C	ASTM D92	224
CCS @ -25°C, cP	ASTM D5293	5106

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.